

IR ILLUMINATOR



► FEATURES

- Special structural design for heater eliminating

► SPECIFICATIONS

Model Name	NT-IR15	NT-IR30	NT-IR60
IR Distance	15 meters	30 meters	60 meters
IR LED	CAT'S EYE LED x 6pcs	CAT'S EYE LED x 12pcs	CAT'S EYE LED x 12pcs with condensing lens
IR View Angle	View angle: 80° ,Beam spread:20°~30° /per LED		
IR Wavelength	850nm		
IR Status	Under 10 Lux by CDS auto control		
LED Life	More than 20,000 Hours		
Protection Class	IP 66		
Power Requirement	12VDC		
Power Consumption	IR on: 280mA	IR on: 550mA	
Construction	Aluminum with sun-shield weatherproof		
Operation Temp.	Working: -10~+55°C, Storage: -30~+80°C		
Dimension(mm)	128(W) x 60(H)	250(W) x 95(H)	
Weight	431 g	927 g	

15M

30M/60M

CAMERA HOUSINGS



NT-H600 Series



NT-H700 Series

Bracket (Option)



Standard type



L type bracket

► SPECIFICATIONS

Model Name	NT-H600	HT-H600S	HT-H600S
Plate Glass	5mm		
Construction / Color	Aluminum / Beige		
Clear Windows Area	83x70mm		
Input Voltage	-	AC24V	
Accessory	-	Shield	Heater, Blower
Certificate	CE, IP66		
Dimension	390x142x115mm		
Weight(N. W)	1200g	1500g	1300g
Bracket (option)	Standard bracket		
Packing	6 PCS in one carton / 3.5Cu'ft		

Model Name	NT-H700	NT-H700S	NT-H700H	NT-H700B	NT-H700HB
Plate Glass	4mm				
Construction / Color	Aluminum / Beige				
Clear Windows Area	94x85mm				
Input Voltage	-	-	AC230V	AC230V	AC230V/AC24V
Accessory	-	Shield	Heater	Blower	Heater, Blower
Certificate	CE, IP68, WEEE, RoHS				
Dimension	400x128x127mm				
Weight(N. W)	1800g	2100g	1900g		
Bracket (option)	Standard and L type bracket				
Packing	12 PCS in one carton / 3.5Cu'ft				